Terminal Block for Ring Tongue Connections

	ST 5	ST 5 P	ST 5 S	STL 5
	new	new	new	new
				
	Single Level	**Single Level**	**Single Level**	**Slide Link**
Available Options — **Version**	**Part No.**	**Part No.**	**Part No.**	**Part No.**
Beige PA	**C9000676**	**C9001456**	**0448360000**	**0448460000**
Dimensions				
Width / Length / Height mm (in.) — for TS 32	9.5/42.5/42 (0.37/1.67/1.56)	13/51/41.6 (0.51/2.01/1.64)	16.3/52/45.5 (0.64/2.05/1.79)	16.3/52/45.5 (0.64/2.05/1.79)
Technical Data				
Rated voltage / rated current / wire size — UL	600 V / 35 A / #20…10 AWG	600 V / 45 A / #20…10 AWG	600 V / 65 A / #12…8 AWG	600 V / 65 A / #12…8 AWG
CSA	600 V / 35 A / #22…10 AWG	600 V / 45 A / #22…8 AWG	600 V / 45 A / #12…8 AWG	600 V / 65 A / #22…6 AWG
VDE	-	-	750 V / 85 A / -	250 V / 30 A / -
Torque — Nm (lb. in.)	1.1 (10)	1.1 (10)		
Max. Ring Lug outer dia. mm (in.)			13.97 (.55)	13.97 (.55)
End Plate (AP) / Partition (TW)	**Type** / **Part No.**	**Type** / **Part No.**	**Type** / **Part No.**	**Type** / **Part No.**
(thickness mm)	AP PA (1.5) **C9000686**	AP PA (1.5) **C9001506**	AP PA (1.5) **0447260000**	AP PA (1.5) **0447260000**
Resin bonded paper	TW (0.5) **C47470**	TW (0.5) **C47470**		
Beige PA			TW (1.5) **0477660000**	TW (1.5) **0477660000**
Jumpers / Jumper Links				
Q 2	Q 2 **C9001610**	Q 2 **C9001530**		
	Q 10 **C9001620**	Q 10 **C9001540**		
QL	QL 2 **C9001370**	QL 2 **C9001460**	QL 2 **3834300000**	QL 2 **3834300000**
	QL 3 **C9001380**	QL 3 **C9001470**		
	QL 4 **C9001390**	QL 4 **C9001480**		
	QL 10 **C9000750**	QL 10 **C9001490**		
Final number indicates number of poles. See the Accessories Section for more information. — Sleeve	VH 12.5 **C9000760**	VH 17 **C26700**		
Fixing screw	BS M3.5 x 18 **C9000780**	BS M4 x 30 **C26710**		
Cover (1M)				
Transparent PVC			ADP **0447700000**	ADP **0447700000**
Mounts in groove on Terminal block				

See Accessories section for mounting rails, end brackets, additional marking material and accessories.