



**NOTES:**

1. UL2725 USB 2.0 REV CABLE.(28AWG\*1PAIR + 24AWG X 2C), AL-FOIL AND BRAID SHIELDED(AL) WITH A DRAIN WIRE, BLACK PVC JACKET, OD:  $\phi 4.5 \pm 0.1 \text{mm}$ . (B-U22824-4.5-BK-01-B)
2. CONNECTOR: P1: USB A TYPE MALE, REVERSABLE, GOLD PLATED CONTACTS, NICKEL PLATED SHELL.  
P2: USB A TYPE FEMALE, WHITE PBT INSULATION, GOLD PLATED CONTACTS, NICKEL PLATED SHELL.
3. ALL HOOD: MOLDED BLACK PVC.
4. TEST: 100% ELECTRICAL TESTING.
5. MOLDED NO.: USB-90-AM02,USB-AF05.



A	INITIAL RELEASE				05/15/13
REV	DESCRIPTION OF CHANGE				DATE
TOLERANCE		INCHES		M/M	
.X	.015	.30			
.XX	.010	.10			
.XXX	.005	.05			
		SCALE	NONE		
		UNIT	MM		
		SHEET	1/1		REV A
		DATE	05/15/13		
DRAWN BY		Eric		DWG NO.	
CHECK BY		TITLE			
		USB AM REVERSABLE 90°TO USB AF			
APPD BY		PART NO.		UR024-18N-RA	