

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20  
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
CM	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		D		REVISED PER ECO-11-017731	31AUG11	JR	TM

- FLASH ALLOWANCE TO BE 0.05 MAX HIGH x 0.03 MAX THICK.
- FLASH NOT PERMITTED IN THIS AREA.
- FLASH MAY BE PRESENT ON THIS EDGE. NO FORM, FIT OR FUNCTION ISSUES IF LESS THAN 0.21 LONG.
- INSULATION DIAMETER MUST BE MET REGARDLESS OF WHICH WIRE SIZE IS USED.
- THIS SEAL IS NOT COMPATIBLE WITH 26-30 AWG CONTACTS. 26 AWG WIRE MUST BE USED WITH 22-26 AWG CONTACTS.
- OPTIONAL CONSTRUCTION.

SECTION A-A

3 DIMENSIONAL VIEW  
SCALE 10:1

35.45 mm <sup>3</sup>	BLUE	1.02-2.11	18-26 AWG	1.0	794758-1
VOLUME	COLOR	INSULATION DIAMETER $\triangle 4$	WIRE RANGE $\triangle 4$	DIM A	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN K. WHITAKER 15FEB2001	<b>STE</b> TE Connectivity		
DIMENSIONS: mm		CHK C. JONES 15FEB2001			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD C. JONES 15FEB2001	NAME SINGLE WIRE SEAL, MINI UNIVERSAL MATE-N-LOK(TM)		
0 PLC ±.2 1 PLC ±.2 2 PLC ±. 3 PLC ±. 4 PLC ±. ANGLES ±2° FINISH		PRODUCT SPEC - APPLICATION SPEC -	SIZE A2	CAGE CODE 00779	DRAWING NO 794758
MATERIAL SILICON RUBBER		WEIGHT -	RESTRICTED TO -		
		CUSTOMER DRAWING	SCALE 20:1	SHEET 1	OF 1

1471-9 (3/11)  
Pro/ENGINEER DRAWING