


WIRE, HALOGEN FREE, THIN WALL INSULATED,
300 VOLT AC, TEMPERATURE CLASSIFICATION 105°C

The complete requirements for procuring the wire described herein shall consist of this document.



Part Description	Conductor				Finished Wire			
	Nominal		Diameter (mm)		Maximum Resistance @ 20°C (ohms/km)	Diameter (mm)		Maximum Weight (kg/km)
	Cross Sectional Area (mm ²)	Conductor Stranding No./Diam. (mm)						
100E0111-0.50-*	0.50	19/0.18	0.82	0.90	40.1	1.37	1.45	6.60
100E0111-0.75-*	0.75	19/0.23	1.04	1.15	26.7	1.59	1.65	8.90
100E0111-1.00-*	1.00	19/0.25	1.17	1.26	20.0	1.69	1.80	10.7
100E0111-1.50-*	1.50	37/0.23	1.46	1.58	13.7	2.03	2.13	16.0
100E0111-2.50-*	2.50	37/0.29	1.85	2.01	8.21	2.50	2.63	25.7

COLOUR CODE: The '*' in the part number shall be replaced by a standard colour code designator in accordance with Mil Std 681.
e.g. 100E0111-1.50-0 Black outer jacket

PERFORMANCE REQUIREMENTS: To be tested to and meet the requirements of the issue in effect of EN 50306-2

MARKING REQUIREMENT: Every 250 ± 25 mm
The mark shall be: **TE Raychem EN 50306-2 300V 1 X § M**

Where "§" = The nominal conductor cross-sectional area

APPROVAL: Electronic sign off - no signatures will appear.

"Raychem", "TE" and "Tyco Electronics" are registered trademarks of Tyco Electronics Corporation.

Tyco Electronics UK Ltd
Faraday Road
Dorcan
SWINDON
SN3 5HH
UK
Tel: 0800 267666
Fax: 01793 572516
Registration Number:
550926 London, England
Website: www.tycoelectronics.com
Email: picuk@tycoelectronics.com

This drawing and the information set forth hereon are the property of Tyco Electronics UK Ltd, and are to be held in trust and confidence. Publication, duplication, disclosure or use for any purpose not expressly authorised in writing by Tyco Electronics UK Ltd is prohibited.

This specification sheet takes precedence over documents referenced herein. As Tyco Electronics UK Ltd. reserve the right to make changes in construction without notice please contact Tyco Electronics UK Ltd to ensure that this document is the latest issue