

## Specification Sheet

Part Number: T250R0HIRUVX2



Heavy Duty Cable Tie, 20.3" Long, UL Rated, 250lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg

Article Number	111-24805
Type	T250R
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• High impact, heat and UV stabilized heavy duty cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.</li><li>• Heavy duty design to offer higher tensile strength.</li><li>• Buckle feature on head allows excess strap to be tucked away after installation.</li></ul>
Quantity Per	bag

### Product Description

HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	Heavy Duty Cable Tie, 20.3" Long, UL Rated, 250lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg
<b>Global Part Name</b>	T250R-PA66HIRHSUV-BK
<b>Minimum Tensile Strength (Imperial)</b>	250.0
<b>Minimum Tensile Strength (Metric)</b>	1115.0
<b>Length L (Imperial)</b>	20.3
<b>Length L (Metric)</b>	515.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.49
<b>Width W (Metric)</b>	12.4
<b>Bundle Diameter Min (Imperial)</b>	0.47
<b>Bundle Diameter Min (Metric)</b>	12.0
<b>Bundle Diameter Max (Imperial)</b>	4.9
<b>Bundle Diameter Max (Metric)</b>	124.5

<b>Thickness T (Imperial)</b>	0.075
<b>Thickness T (Metric)</b>	1.9
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +230°F (-40°C to +110°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL   ANSI/UL 62275 UL   ANSI/UL 746B UL   ANSI/UL 1565
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	25
<b>Package Quantity (Metric)</b>	25
<b>Customs Number</b>	3926909987

**Content Unit(BMEcat)**

pcs.

**Weight (Metric)**

16.33