

## Waber-by-Tripp Lite Surge Suppressor with heavy-duty metal housing

MODEL NUMBER: **DG115-SR**



### Highlights

- 6 outlets/6 ft. cord
- 600 joule rating
- Audible surge indication
- Remote switch included

### Package Includes

- DG115-SR Power Strip
- Warranty information
- Instruction manual

### Description

The Waber-by-Tripp Lite DG115-SR Power Strip offers a convenient method of power distribution and surge suppression in workbench, wallmount or floor mount applications. Unique design includes remote power switch at the end of a 6 foot cord allows remote power control of connected equipment. Includes 6 NEMA 5-15R output receptacles, 6 foot AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built in surge suppression rated at 600 joules. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features metal housing, lighted power switch with integrated 15 amp resettable circuit breaker and attractive gray color scheme. Lifetime warranty.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 6 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip with remote power switch on a 6 ft. cord

SUPPRESSION - 600 joules AC suppression

### Features

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Mountable remote power switch at the end of a 6 foot cord allows remote power control of connected equipment.
- Includes 6 NEMA 5-15R output receptacles
- Lighted combination power switch with integrated circuit breaker
- Keyhole mounting tabs support permanent installation on a wide variety of surfaces
- UL1449 (USA/400V rating), UL1363 (USA), cUL (Canada)
- 15 amp power handling capacity
- 6 foot AC line cord
- Lifetime warranty



## Specifications

| OVERVIEW                          |   |
|-----------------------------------|---|
| UPC Code                          | 037332115621  |
| OUTPUT                            |   |
| Frequency Compatibility           | 50 / 60 Hz  |
| Output (Watts)                    | 1800  |
| Circuit Breaker (amps)            | 15  |
| INPUT                             |   |
| Recommended Electrical Service    | 120V (110-125V)   |
| Input Connection Type             | NEMA 5-15P input plug   |
| Input Cord Length (ft.)           | 6   |
| Input Cord Length (m)             | 1.83  |
| Input Cord Gauge Type             | 14 gauge, SJT   |
| Voltage Compatibility (VAC)       | 120   |
| USER INTERFACE, ALERTS & CONTROLS |   |
| Switches                          | Lighted two position mountable remote power switch at the end of a dedicated 6 ft. cord controls power to all outlets |
| Diagnostic LED Details            | Protection present (green)  |
| SURGE / NOISE SUPPRESSION         |   |
| AC Suppression Joule Rating       | 600   |
| AC Suppression Response Time      | < 1 ns  |
| Protection Modes                  | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression                                    |
| UL1449 Let Through Rating         | 400V - UL Verified  |
| EMI / RFI Filtering               | Up to 20dB  |
| Immunity                          | Conforms to IEE 587 / ANSI C62.41   |
| DATALINE SURGE SUPPRESSION        |   |
| Telephone/DSL Protection          | No  |
| Cable (Coax) Protection           | No  |
| Network (Ethernet) Protection     | No  |
| PHYSICAL                          |   |
| Shipping Dimensions (hwd / in.)   | 2.16 x 15.00 x 6.00   |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                     |  |
|-------------------------------------|--|
| Shipping Dimensions (hwd / cm)      | 5.50 x 38.10 x 15.24                       |
| Shipping Weight (lbs.)              | 2.12                                       |
| Shipping Weight (kg)                | 0.96                                       |
| Unit Dimensions (hwd / in.)         | 12.5 x 2.5 x 1.5                           |
| Unit Dimensions (hwd / cm)          | 31.75 x 6.35 x 3.8                         |
| Material of Construction            | Metal                                      |
| Integrated Keyhole Mounting Tabs    | Keyhole mounting tabs enable wall mounting |
| Receptacle Color                    | Gray                                       |
| Color (AC Line Cord)                | Gray                                       |
| <b>CERTIFICATIONS</b>               |  |
| UL1449 3rd Edition (AC Suppression) | UL1449                                     |
| UL1363 (Power Tap)                  | UL1363                                     |
| cUL / CSA (Canada)                  | cUL  |
| <b>WARRANTY</b>                     |  |
| Product Warranty Period (Worldwide) | Lifetime limited warranty                  |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>