



RESISTANCE @ +25°C = 1 Ω ± 25%
 MAXIMUM STEADY STATE CURRENT = 30 AMPS
 RESISTANCE @ MAXIMUM CURRENT = 0.015 Ω NOMINAL
 DIM "D" = 1.475" MAXIMUM
 DIM "T" = 0.350" MAXIMUM
 DIM "L" = 0.850" MINIMUM
 DIM "S" = 0.310" NOMINAL
 LEAD GAUGE = 18 AWG

SEE MANUFACTURING SPECIFICATION (LAYER 1)

"A"	DIM "D" WAS 1.250" MAXIMUM, DIM "L" WAS 1.0" MINIMUM, DIM "T" WAS 0.250" MAXIMUM & REMOVED VOLTAGE RATING OF 265 Vrms	07/14/09	DD
---	ISO RELEASE	01/26/04	DD
REV	REVISION RECORD	DATE	APP

SCALE	NONE	U.S. SENSOR CORP. 1832 W. COLLINS AVE. ORANGE, CA 92867 714-639-1000 www.ussensor.com
DRAWN BY	T. SOMERVILLE	
DATE	07/23/90	
REV.	"A"	
LAYER	0 OF 2	
		INRUSH CURRENT LIMITER
		P/N ST1R030B