

## Specification Sheet

Part Number: 170-03175



Braided Sleeving, Aluminum Laminated Fiberglass, .38" Dia, AL/GF, Silver, 100 ft/reel

<b>Article Number</b>	170-03175
<b>Type</b>	BSHTTST38SR
<b>Color</b>	Silver (SR)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.</li><li>• Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.</li><li>• Cuts with ordinary scissors for fast, easy application.</li></ul>
<b>Quantity Per</b>	reel
<b>Product Description</b>	A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.
<b>Short Description</b>	Braided Sleeving, Aluminum Laminated Fiberglass, .38" Dia, AL/GF, Silver, 100 ft/reel

Global Part Name

BSHTTST38SR-AL/GF-ML

Length L (Imperial)

100.0

Length L (Metric)

30.48

Bundle Diameter Min (Imperial)

0.1

Bundle Diameter Min (Metric)

2.54

Bundle Diameter Max (Imperial)

0.437

Bundle Diameter Max (Metric)

11.1

Diameter D (imperial)

0.38

Diameter D (metric)

9.7

Nominal Diameter (Imperial)

3/8

Nominal Diameter (Metric)

9.7

Wall Thickness WT (Imperial)

0.025

Wall Thickness WT (Metric)

0.64

Material

Aluminum (AL) Glass Fiber (GF)

Material Shortcut

AL GF

<b>Flammability</b>	Non-Flammable
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-76°F to +491°F (-60°C to +255°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	30.48
<b>Customs Number</b>	3926909987
<b>Weight (Metric)</b>	1.1
<b>Weight (Imperial)</b>	2.3
<b>Reel Weight (Imperial)</b>	2.25
<b>Reel Weight (Metric)</b>	1.02