



File: E209153



ISO9001:2008 Certified

Mechanical Specifications (mm)

| | |
|---|---|
| D: | ± |
| T: | ± |
| Lead Diameter | ± |
| S: | ± |
| L: | ± |
| Coating Lead Run Down (straight Leads) | ± |
| B: | ± |
| C: | ± |



Electrical Specifications

| | | |
|---------------------------------------|---------|--------|
| Resistance: | 150.0 Ω | ± 25 % |
| Max Steady State Current upto 65°C: | 2.00 | A |
| Max Rec. Energy Rating: | 10 | J |
| Actual Failure Instantaneous Energy: | 30 | J |
| Resistance @ 100% Max Current: | 0.96 | Ω |
| Resistance @ 50% Max Current: | 1.92 | Ω |
| Body Temperature at 100% Max Current: | 137.00 | °c |
| Dissipation Constant: | 11.4 | mw/°c |
| Thermal Time Constant: | 40 | Sec. |
| Material Type (for Beta and Curve): | M | |

| SL12 15102 | |
|--|--------------------------|
| Date: 10/08/2012 | Drawn by: Erin Landis |
| Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com | Approved By: Mehdi Samii |
| | Revision: A |