

APPLICATOR PARTS LIST				TYPE SIDE FEED STRIPPER CRIMPER			AMP INCORPORATED HARRISBURG, PENNA.					
NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	CRIMPING DATA			TERMINALS	
1	WIRE CRIMPER	1	694862-9	42				TO APPLY TERMINAL .093 DIA RECEPTACLE			350221	
2	INS. CRIMPER	1	454686-3	43				WIRE SIZE	CRIMP HEIGHT			
3	ANVIL	1	2-565063-3	44	Wire Grip - Lower	1	Ref 694817-2	.26	.029			
4	Stabilizer			45	Retainer, Strip	1	454739-2	.28	.029			
5	SHEAR, Floating	1	1-694851-2	46	Post, Retainer	1	694868-1					
6	REAR SHEAR PLATE			47								
7	SHEAR BLADE SPACER			48								
8	FRONT SHEAR PLATE			49								
9	REAR ANVIL SPACER PLT.			50	Lever	1	694811-3	CRIMP	SIZE	TYPE	FEED	
10	FRONT ANVIL SPACER PLT.			51				WIRE	.055	F	.405	
11	TOOL SPACER	1	694839-5	52				INSUL.	.090	F		
12	CRIMP SPACER	1	1-694839-0	53				SLEEVED				
13	Stabilizer Spacer			54				INSULATION RANGE	WIRE RANGE			
14	REAR STRIP GUIDE			55				.032-.057	26-28			
15	RAM			56				EXPLODED VIEW CM 5210 Sect. 9				
16	TOOL HOLDER			57				REMARKS				
17	Crimper Holder	1	694856-1	58				1 Position between items 1 & 2				
18	ADJ. BLOCK			59	Rear Shear Assy.			2 See Customer Manual for orientation.				
19	APPLICATOR MOUNT ASSY.			60	Applicator Assy.	1	694861-7	3 Sequence from Ram: 11, 7, 12, 17(2)				
20	BASE PLATE			61	Blade, Strip LH = 26	1	462218-8					
21	BASE BLOCK			62	Blade, Strip RH = 26	1	462217-8					
22	STRIP GUIDE PLATE	1	453309-7	63	Stabilizer, Wire	1	453262-3					
23	ANVIL HOLDER			64								
24	AUX. ANVIL HOLDER			65								
25	STRIPPER	1	694829-1	MISCELLANEOUS								
26	STRIPPER MOUNT			66	Identification Plate	1	452373-1					
27	RETAINER PLATE			67	Lubricator Assy.	1	465181-3					
28	STRIPPER MOUNT BRACKET			68	Oil, Synthetic	REF	462931-2					
29	STRIPPER BUSHING			69	Grease, High Pressure	1	24482-2					
30	STOCK DRAG	1	2-6948263	70								
31	STOCK DRAG HANDLE			71								
32	STOCK DRAG STUD			72								
33	STOCK DRAG SPRING			REV.	REVISION RECORD	DATE	BY	ECN				
34	STOCK DRAG ADJ. SCREW			A	Redrawn	7-3-75	RT	R1198				
35	FEED FINGER HOLDER			B	Rev per ECN	4-1-76	RT	R165				
36	FEED FINGER			B1	INACTYATED	7-28-76	RT	R178				
37	FEED FINGER TIP			C	EC-A-272490	10-10-79	JW	—				
38	FEED FINGER SPACER			D	EC A-360692	4-2-92	JW	—				
39	BASE CASTING											
40	GUARD											
41												

— INACTIVE —
FOR REPLACEMENT ONLY

DENOTES WEARING PARTS
RECOMMEND PURCHASE REPLACEMENT

THIS APPLICATOR IS TO BE USED ON
AMP-ELECTRIC 694873-1

SERIAL NO. _____ DATE SHIPPED _____
 CUSTOMER NAME AND ADDRESS _____
 APPLICATOR NUMBER **D 566173-1**

DESIGNED BY **7/3/75**
 DRAWN BY **7-75**
 CHECKED BY **7/3/75**
 SHEET **1** OF **1**