





IC Socket 2.54mm(0.100")

Specifications

Contact Resistance: 30 mohms max. at DC 100mA
 Insulator Resistance: 1000 megohms min. at DC 500V
 Current Rating: 1 Amp
 Dielectric Withstanding Voltage: AC 500V for 1 minute
 Operating Temperature: -55^o~+105^oC
 Contact: Phosphor Bronze
 Housing: PBT & 30% Glass Fiber (UL 94V-0)

Dimensions

No. of Contacts	Qty per Tube	A	B	C
06	80	7.62	10.0	7.62
08	60	10.16	9.96	7.62
14	34	17.78	9.96	7.62
16	30	20.32	9.96	7.62
18	26	22.86	9.96	7.62
20	24	25.40	9.96	7.62
22	21	27.94	9.96	7.62
22*	21	27.94	12.62	10.16
24	20	30.48	17.68	15.24
24**	20	30.48	17.68	7.62
28	17	35.56	17.68	15.24
28**	17	35.56	17.68	7.62
32	15	40.64	17.68	15.24
40	12	50.80	17.68	15.24



Recommended P.C.B. Layout

RoHS
Compliant

Description	
Name: AXX-LC-TT-R	
Low Cost IC Socket 2.54mm, Straight Leg	

THIS DRAWING IS UNPUBLISHED
 © Copyright 2005 by Assmann Electronic Components All International Rights Reserved
 This drawing is a controlled document for Assmann Electronics, Inc. It is subject to change and the controlling engineering organization should be contacted for the latest revision.