


Contact assignment:

- 1) brown
- 2) white
- 3) blue
- 4) black
- 5) grey



Technical specification:

Rated voltage: 60 V
IEC 61076-2-101

Current rating: 4 A at 40°C
IEC 61076-2-101

Insulation resistance: >=100 MΩ
IEC 60512

Pollution degree: 3/2
IEC 60664-1

Degree of protection: IP 67, in mated condition
IEC 60529

Temperature range: -30°C ... +80°C

Mating cycles: >=100
IEC 60512-9a

Materials:

Contact: CuZn

Contact plating: Nickel, gold plated

Contact carrier: PBT GF, UL 94

Sealing: FPM


Socket housing: CuZn, nickel plated

Grouting: Polyurethane-resin, UL 94

Installation specification:

recommended torque: 1-1,2 Nm

Conec installation tool: Torque wrench: 36-000200
Insert across flats 17: 36-000230



Minimum wall thickness 1,5mm,
alternativ panel cut-out d=15,3

Part no:	Description:	Pos	Length L:	Wire:
43-01074	SAL - 12 - FK5.1 - 0,5 - 9	5	0,5m	AWG 24 PVC, UL
43-xxxxx	SAL - 12 - FK5.1 - ... - 9	5	x	

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index: c 08.02.13 MG Ä4631 Data sheet revised, technical specification changed, materials corrected	dim. in mm		
	tolerance of wire: L <= 0,5m: L + 20mm L > 0,5m: L + 4%	drawn	06.03.07	Fromm
		appd.	06.03.07	Mankopf
	general tolerance:	0 ± 0,50mm	CONEC ®	
	0,0 ± 0,25mm			
	0,00 ± 0,10mm			

title: Female socket M12x1 with wire, frontmounting, PG9	
dwg no: 43K1A315	
part no:	see table