

## Specification Sheet

Part Number: RT255R0HIRX2



Releasable Cable Tie, Release Tab, 20" Long, 250lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg

Article Number	115-01300
Type	RT255R
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• High impact, heat and UV stabilized releasable cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.</li><li>• Special design offers a release feature for quick and easy access to wire bundles.</li><li>• Head design provides high tensile strength with very low insertion force even after repeated use.</li></ul>
Quantity Per	bag

### Product Description

HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	Releasable Cable Tie, Release Tab, 20" Long, 250lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg
<b>Global Part Name</b>	RT255R-PA66HIRHSUV-BK
<b>Minimum Tensile Strength (Imperial)</b>	250.0
<b>Minimum Tensile Strength (Metric)</b>	1115.0
<b>Length L (Imperial)</b>	20.0
<b>Length L (Metric)</b>	508.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	Yes
<b>Width W (Imperial)</b>	0.5
<b>Width W (Metric)</b>	12.6
<b>Bundle Diameter Min (Imperial)</b>	0.49
<b>Bundle Diameter Min (Metric)</b>	12.5
<b>Bundle Diameter Max (Imperial)</b>	5.0
<b>Bundle Diameter Max (Metric)</b>	127.0
<b>Cable Tie Width Max (Imperial)</b>	0.49
<b>Cable Tie Width Max (Metric)</b>	12.5

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +230°F (-40°C to +110°C)
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL-ZODZ2.E64139
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	25
<b>Package Quantity (Metric)</b>	25
<b>Customs Number</b>	3926909987