


24-Outlet Vertical Power Strip, 120V, 20A, L5-20P, 15-ft. Cord, 72 in.

MODEL NUMBER: **PS7224-20T**



Highlights

- 24 outlets
- Convenient and safe covered, on/off switch
- 20-amp circuit breaker
- 15 ft. cord with locking L5-20 input plug
- 72" length

Package Includes

- PS7224-20T
- Mounting hardware
- Instruction manual

Description

Tripp Lite's PS7224-20T power strip offers 20 amp, 120V multi-outlet AC power distribution in a convenient 72 inch mountable housing with NEMA L5-20 locking input plug. Offers horizontal or vertical power distribution in rackmount, raceway and workbench applications. Includes 24 output receptacles with 2.795 inch center-to-center spacing, 15 ft AC line cord and lighted power switch with locking transparent cover to prevent accidental shutoff. Sturdy all-metal extruded aluminum housing stands up to demanding network, laboratory or factory environments.

INPUT/OUTPUT: Input: NEMA L5-20P (twist lock)/Output: 22 NEMA 5-15R & 2 NEMA 5-20R

ELECTRICAL: 120V AC, 50/60Hz, 20A

FORMAT: 72 in. corded, mountable power strip

Features

- Sturdy all-metal 72 inch corded strip format with 2.795 inch center-to-center outlet spacing
- Included mounting hardware supports vertical or horizontal mounting in rack enclosures, raceways and more
- Includes 22 NEMA 5-15R and 2 NEMA 5-20R output receptacles
- Includes NEMA L5-20 twist-lock input plug connection
- Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications
- Lighted power switch with locking transparent cover prevents accidental shutoff
- 20 amp electrical capacity with circuit breaker
- 120V AC, 50/60Hz electrical compatibility

Specifications

OVERVIEW



| | |
|--|---|
| UPC Code | 037332042378 |
| OUTPUT | |
| Frequency Compatibility | 50 / 60 Hz |
| Output Receptacles | (2) 5-15/20R; (22) 5-15R |
| Output (Watts) | 2400 |
| Circuit Breaker (amps) | 20 |
| Outlet Spacing | 2.795 in. |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 20A 120V |
| Input Connection Type | NEMA L5-20P |
| Input Plug Features | Black |
| Input Cord Length (ft.) | 15 |
| Input Cord Length (m) | 4.57 |
| Input Cord Gauge Type | 12/3 SJT |
| Voltage Compatibility (VAC) | 120 |
| USER INTERFACE, ALERTS & CONTROLS | |
| Switches | Lighted 2 position switch controls power to all outlets |
| Locking Switch Cover | Transparent on/off switch cover prevents accidental turn-off |
| PHYSICAL | |
| Shipping Dimensions (hwd / in.) | 3.50 x 2.50 x 76.00 |
| Shipping Dimensions (hwd / cm) | 8.89 x 6.35 x 193.04 |
| Shipping Weight (lbs.) | 6.10 |
| Shipping Weight (kg) | 2.77 |
| Unit Dimensions (hwd / in.) | 72 x 1.5 x 1.5 |
| Unit Dimensions (hwd / cm) | 183 x 3.8 x 3.8 |
| Unit Weight (lbs.) | 6.6 |
| Unit Weight (kg) | 2.99 |
| Material of Construction | Aluminum |
| Included Mounting Accessories | Includes mounting clips |
| Receptacle Color | Black |
| Color (AC Line Cord) | Black |
| Form Factors Supported | Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|--|---------------------------|
| Outlets Measurement (Center to Center) | 72mm |
| CERTIFICATIONS | |
| UL1363 (Power Tap) | UL1363 |
| cUL / CSA (Canada) | cUL |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>