

## Specification Sheet

Part Number: 556-26007

**HellermannTyton** TipTag, 3.54" x .50", PO/Polyester, White/Yellow, 500/roll

<b>Article Number</b>	556-26007
<b>Type</b>	TIPTAGVA10X90YEW
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>•Halogen free for low-smoke and low-fire hazard applications.</li><li>•White front and yellow back for versatility.</li><li>•Superior strength and tear resistance for long lasting identification.</li><li>•Pre-cut slots to secure the TipTags using HellermannTyton cable ties.</li></ul>
<b>Quantity Per</b>	pack
<b>Product Description</b>	TIPTAGs are halogen free, tear resistant, and lightweight cross laminated polyolefin tags ideal for use where weight is a critical factor. Each side is a different color. One side is yellow and the other side is White so that a high contrast black on yellow or black on white mark can be printed.
<b>Short Description</b>	TipTag, 3.54" x .50", PO/Polyester, White/Yellow, 500/roll

Global Part Name

TIPTAGVA10X90YEWB-PO-BK

Variant	Other
Width W (Imperial)	3.54
Width W (Metric)	90.0
Height H (Imperial)	0.5
Height H (Metric)	12.7

Material	Polyolefin (PO)
----------	-----------------

Material Shortcut PO

US MIL SPEC	MIL-STD-202G Method 215K
-------------	--------------------------

SAE-AS81531  
Halogen free

Yes	Operating Temperature (Metric)
-58°F to +221°F (-50°C to +105°C)	Reach Complaint(Article 33)
Yes	ROHS Complaint
Yes	Certification/Specification WEB

SAE - AS81531 BS-4G-198-3, Type 11a MIL-STD-202G Method 215K

<b>Package Quantity(Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3921905050
<b>Content Unit(BMEcat)</b>	reel
<b>Weight (Metric)</b>	0.26
<b>Weight (Imperial)</b>	0.649