



N-07-50-MH-9-C-XX

ⓓ

N = CABLE TIES

CABLE TIE LENGTH
INCHES
(ROUNDED)

TENSILE STRENGTH
18 = 18 LBS
40 = 40 LBS
50 = 50 LBS
120 = 120 LBS

TIE TYPE
(BLANK) = STANDARD TIE
ID = IDENTIFICATION
MH = MOUNTING HOLE

INTERNAL DESIGNATOR

AMOUNT PER PACKAGE
C = 100
D = 500
M = 1000

COLORS
0 = UV BLACK
9 = NATURAL
30 = HEAT STABILIZED

SALES DRAWING

| | | | | | | | |
|--|-----------------|---------------------------------------|-------|---|----------------------|---|------------------------------|
| REMOVE BASE INFO EC NO: ETC2007-0295 DRWN: TBOANN02007/02/13 CHKD: JMACNEIL 2007/02/13 APPR: JMACNEIL 2007/02/14 | QUALITY SYMBOLS | GENERAL TOLERANCES (UNLESS SPECIFIED) | | SCALE NTS | DESIGN UNITS INCH | THIRD ANGLE PROJECTION | REVISE ON CAD ONLY |
| | DESCRIPTION | mm | INCH | DIMENSION STYLE IN/MM | | TITLE | |
| | ▽ = 0 | 4 PLACES ± --- | ± --- | DRAWN BY B.ENDERL | DATE 04/05/11 | 19252 SERIES ENGINEERING NUMBERS CABLE TIES | |
| | ∇ = 0 | 3 PLACES ± --- | ± --- | CHECKED BY H.BEITZL | DATE 04/05/11 | MOLEX INCORPORATED | |
| REV | | 2 PLACES ± --- | ± --- | APPROVED BY R.DEROSS | DATE 04/05/11 | MATERIAL NO. SEE CHART | DOCUMENT NO. SD-19252-001 |
| | | 1 PLACE ± --- | ± --- | DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | SHEET NO. 1 OF 1 | |
| | | ANGULAR ± ---° | | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | | |