

DIN rail perforated - NS 35/15 BLK PERF 2000MM - 1208018

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



DIN rail perforated, Standard profile, width: 35 mm, height: 15 mm, similar to EN 60715, material: Steel, uncoated, length: 2000 mm, color: white aluminum



Key Commercial Data

| | |
|--------------|---------------|
| Packing unit | 5 STK |
| GTIN | |
| GTIN | 4017918155582 |

Technical data

Dimensions

| | |
|--------------------|----------|
| Height | 15 mm |
| Length | 2000 mm |
| Width | 35 mm |
| Hole width | 15.00 mm |
| Hole height | 6.20 mm |
| Drill hole spacing | 25.00 mm |

General

| | |
|----------|----------------|
| Material | Steel |
| Coating | uncoated |
| Color | white aluminum |


Standards and Regulations

| | |
|----------------------------------|---------------------|
| Test standard | similar to EN 60715 |
| Connection in acc. with standard | IEC / EN |

Drawings

DIN rail perforated - NS 35/15 BLK PERF 2000MM - 1208018

Dimensional drawing



Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>