



Shellsize	A	B	C	D	E	F <sup>+1</sup> <sub>-3</sub>	G	Cable Ø	Part-NO.
1	40.76	25.00	SW 20	51.0	22.0	77.0	44.0	5 - 10	165X15319X
2	49.06	33.30	SW 24	51.0	22.0	79.0	52.0	7 - 12	165X15329X
3	62.80	47.04	SW 24	59.5	22.0	87.5	52.0	7 - 12	165X15339X
4	78.86	63.50	SW 30	67.0	22.0	99.0	52.0	9 - 16	165X15349X
5	76.46	61.10	SW 40	67.0	24.8	107.0	52.0	13 - 20	165X15359X

Directive 2002/95 EC  
 „RoHS“  
 Compliant

**NOTES:**  
 1. HOOD: ABS V0, METALLIZED  
 2. SCREWS: STAINLESS STEEL

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH			
DO NOT ALTER CAD DRAWING BY HAND			
2 x b	Ä 3353	29.04.2009	Lehmen
a	Origin		
rev.	description	date	name

tolerance		dim. in mm	scale: 1:1
			material: SEE NOTES
2004	date	name	<b>WATER RESISTANT D-SUB HOOD</b> 9-50pos. with jack screw
drawn	15.08.	Lehmenkühler	
appd.	15.08.	Kühle	
norm			dwg no: AutoCAD 2004 DIN-A 3 sh: 1/1
d-old			
			part no: SEE TABLE