

PIN RECEPTACLES

FOR 0,56 - 0,86 DIAMETER PINS AND 0,64 SQUARE PINS

<p>9808 9808-0-15-XX-16-XX-04-0 Press-fit in 1,70 mounting hole</p>	<p>9101 9101-0-15-XX-16-XX-10-0 Press-fit in 1,70 mounting hole</p>	<p>5650 5650-0-19-XX-16-XX-10-0 Press-fit in 1,70 mounting hole</p>	<p>8679 8679-0-15-XX-16-XX-10-0 Solder mount in 1,80 min. mounting hole</p>
<p>6021 6021-0-15-XX-16-XX-10-0 Solder mount in 1,57 min. mounting hole Also available on 24mm wide carrier tape: 1,500 parts per 330mm reel Order as: 6021-0-57-XX-16-XX-10-0</p>	<p>1873 1873-0-15-XX-16-XX-04-0 Press-fit in 1,68 mounting hole</p>	<p>8827 8827-0-15-XX-16-XX-04-0 Press-fit in 1,55 mounting hole</p>	<p>5070 5070-0-18-XX-16-XX-10-0 Press-fit in 1,55 mounting hole</p>

SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard
Contact Material: Beryllium Copper Alloy 172, HT
Dimensions: Millimeters
Tolerances On: Lengths: ±0,13
 Diameters: ±0,051
 Angles: ±2°



ORDER CODE: XXXX - X - XX - XX - 16 - XX - 10 - 0

BASIC PART #

SPECIFY SHELL FINISH:

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 15 0,25µm GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 27 0,76µm GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

#16 CONTACT (DATA ON PAGE 256)

(For alternate contact choices, see group D on page 248)

