



#### General ordering data

Order No.	1718431044
Part designation	TM-I 18 BLANK WS
Version	Conductor markers, L x W: 18 x 4 mm, Polyamide 66, white
EAN	4008190349011
Qty.	320 pc(s).

#### Markings

Cadmium	no
Can be labelled with thermal transfer printers	No
Can be printed with plotter	Yes
Can be written with dot-matrix printer	No
Can be written with laser printer	No
Conductor O.D., max.	40 mm
Conductor O.D., min.	1 mm
Conductor cross-section, max.	500 mm <sup>2</sup>
Conductor cross-section, min.	0.22 mm <sup>2</sup>
Halogen	no
Height	2 mm
Insulation cross-section, max.	40 mm
Length	18 mm
Material	Polyamide 66
Material colour	white
Material colour according to resistance code	9
Max. temperature, continuous	100 °C
Min. temperature, continuous	-40 °C
Pin can be written (STI)	Yes
PrintJet	Yes
Printed characters	without
Silicone	no
Speed marking laser	Yes
Type of printing	Neutral
UL 94 flammability class	V2
Width	4 mm

## Markings

## Approvals

Approvals institutes

n.a.

## Classifications

eClass 4.1	24-19-02-19
eClass 5.0	27-14-91-03
eClass 5.1	27-14-91-03

## Similar products

Order No.	Part designation	Version
1714101044	VT-TM-I 18 BLANK WS	Conductor markers, L x W: 18 x 4 mm, Polyamide 66, white
1714101687	VT-TM-I 18 BLANK GE	Conductor markers, L x W: 18 x 4 mm, Polyamide 66, yellow
1714101693	VT-TM-I 18 BLANK BL	Conductor markers, L x W: 18 x 4 mm, Polyamide 66, Blue
1714101688	VT-TM-I 18 BLANK GN	Conductor markers, L x W: 18 x 4 mm, Polyamide 66, green
1714101690	VT-TM-I 18 BLANK OR	Conductor markers, L x W: 18 x 4 mm, Polyamide 66, Orange
1714101686	VT-TM-I 18 BLANK RT	Conductor markers, L x W: 18 x 4 mm, Polyamide 66, red
1718431693	TM-I 18 BLANK BL	Conductor markers, L x W: 18 x 4 mm, Polyamide 66, Blue
1718431687	TM-I 18 BLANK GE	Conductor markers, L x W: 18 x 4 mm, Polyamide 66, yellow
1718431688	TM-I 18 BLANK GN	Conductor markers, L x W: 18 x 4 mm, Polyamide 66, green
1718431686	TM-I 18 BLANK RT	Conductor markers, L x W: 18 x 4 mm, Polyamide 66, red