



- NOTES
- ① THE RECOMMENDED TIGHTENING TORQUE OF REF. NO. ④ : 0.9 TO 1 N · m.
 THE RECOMMENDED ADHESIVE OF REF. NO. ④ : LOCTITE 243 MADE BY HENKEL JAPAN LTD.
 - ② THE RECOMMENDED TIGHTENING TORQUE OF REF. NO. ⑫ : 0.9 TO 1 N · m.
 THE RECOMMENDED ADHESIVE AND PRIMER OF REF. NO. ⑫ : LOCTITE 243 AND LOCK PRIMER 7649 MADE BY HENKEL JAPAN LTD.
 - ③ ROTATION EXAMPLE ARE SHOWN FOR REF. NO. ①, ④, ⑨, AND ⑫.
 - ④ THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFER, DEPENDING ON THE CABLE STRUCTURE.
 PLEASE CONFIRM BEFORE THE USE.

5	STAINLESS STEEL		12	POLYPHENYLENE SULFIDE (BLACK)	UL94V-0			
4	ZINC ALLOY	NICKEL PLATING	11	POLYAMIDE (WHITE)	UL94V-0			
3	ZINC ALLOY	NICKEL PLATING	10	HYDROGENATION ACRYLONITRILE BUTADIENE RUBBER	(BLACK)			
2	PHOSPHOR BRONZE	CONTACT AREA : GOLD 0.2μm min. TERMINAL AREA : GOLD FLASH. UNDER PLATING : NICKEL 2μm min.	9	ALUMINIUM ALLOY	NICKEL PLATING			
			8	ACRYLONITRILE BUTADIENE RUBBER	(BLACK)			
			7	ACRYLONITRILE BUTADIENE RUBBER	(BLACK)			
1	POLYPHENYLENE SULFIDE (BLACK)	UL94V-0	6	PHOSPHOR BRONZE	NICKEL PLATING			
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS			
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
APPROVED : HY. KOBAYASHI 18.02.26			DRAWING NO. EDC-115626-31-00					
CHECKED : HY. KOBAYASHI 18.02.26			PART NO. HR08D-12WLPA-10S(31)					
DESIGNED : DS. MATSUNE 18.02.24			CODE NO. CL108-0221-9-31					
DRAWN : AI. NISHIYAMA 18.02.16					1/1			