

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	16JUN2015	DL	CW

Top view of the assembly showing dimensions and features. Dimensions include a height of 45 mm, a width of 104 mm, and a total width of 132 mm. Features include 4-Ø5.5 holes and 4-M3 holes. The STS logo is visible on the side panels.

3D perspective view of the assembly, showing its rectangular shape, mounting feet, and the circular opening on the front panel.

Front, side, and detail views of the assembly. The front view shows a width of 56.6 mm and a height of 20 mm. The side view shows a length of 120 mm, a width of 74 mm, and a height of 47 mm. The detail view shows a width of 43 mm and a height of 20 mm. Features include IG2 and IG1 mounting points.

NOTES:

1. TECHNICAL CHARACTERISTICS:
 BODY MATERIAL: DIE CAST ALUMINIUM ALLOY
 SURFACE TREATMENT: POWDER-COATED, GRAY
 OPERATION TEMPERATURE: -40-+125°C
 DEGREE OF PROTECTION: IP65 (MATED)

注释:

1. 技术参数:
 主体材料: 铝合金
 表面处理: 粉末喷涂, 灰色
 工作温度: -40-+125°C
 防护等级: IP65(配合)

TI450240121-000	H24B-SGR-BO-PG21	PG21	-
TI450242125-000	H24B-SGR-BO-PG21/M25	PG21	M25
ASSEMBLY PART NUMBER	ASSEMBLY PART DESCRIPTION	IG1	IG2

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	16JUN2015	 TE Connectivity	
		DAVID LI	16JUN2015		
		CHK	CHRIS WANG		
		APVD	XU XIANG		
		PRODUCT SPEC	108-137013	NAME	
		APPLICATION SPEC	114-137013	H24B-SGR-BO-PG	
MATERIAL		WEIGHT	-	SIZE	RESTRICTED TO
-				A3	-
FINISH		CUSTOMER DRAWING		SCALE	SHEET
-				3:4	1 OF 1
				REV	A

1470-19 (3/13)