

# HORIZONTALLY POLARIZED SECTOR ANTENNA SAH24-120-12



## 2400-2500 MHz, 13 dBi HORIZONTALLY POLARIZED SECTOR ANTENNAS

The Laird Technologies SAH24-120-12 2.5 GHz horizontally polarized 120° sector antenna operates in the 2.4 to 2.5 GHz frequency band with a 13 dBi gain. Especially useful in spectrally crowded areas, the antenna provides a cost-effective solution for WLL, MMDS and point-to-multipoint applications. Optimized for low cross-polarization and low sidelobes, the SAH24-120-12 is ETSI SS compliant.

### FEATURES


- High discrimination of vertically polarized signals
- 120° of horizontal beamwidth
- Horizontal polarization 13 dBi of gain
- Antenna offers durable construction
- Super rugged and lightweight

### MARKETS

- 2.4 GHz ISM band applications
- 802.11b and 802.11g wireless systems
- WLAN base station antennas
- Wireless broadband systems
- Wireless internet
- WiMAX


PARAMETER	SPECIFICATIONS
Frequency Range	2400 - 2500 MHz
Gain	13 dBi
Maximum VSWR	1.5:1, Typical
3 dB Beamwidth - Azimuth	120°
3 dB Beamwidth - Elevation	15°
Polarization	Linear, Horizontal
Lightning Protection	DC – Grounded
Maximum Input Power	100 W
Input Impedance	50 ohm
Front-to-Back Ratio	25 dB
Cross-Polarization	30 dB
Mechanical Size	557 mm x 376 mm x 95.2 mm
Weight	3.4 kg (No Bracket)
Connector	Type N, Female
Radome	Polycarbonate, White
Mounting Style	Mast Mount
Mounting Hardware	Tilt Mount Kit, 1.5 in to 4.5 in Diameter
Temperature Range (Operational)	-30°C to +70°C
Temperature Range (Storage)	-40°C to +85°C

### ANTENNA PATTERNS



### SYSTEM ORDERING

SAH24-120-12 13 dBi 2.4 GHz horizontally polarized sector antenna



Mounting Kit: JBXRK-01-TM5

global solutions: local support.™

Americas: +1.847.839.6907  
IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12  
IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022  
IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANT-DS-SAH24-120-12 0611

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2011 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trademarks or registered trademarks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.