



- 1 USE A P.C.B. WHOSE ARE TREATED WITH SOLDER RESIST.
- 2 SHOW P.C.B LAYOUT FROM ON BOARD SURFACE SIDE.
- 3 NUMBER THE CONTACT IN THE P.C.B OR CONNECTOR CONSECUTIVELY FROM "DATUM" SIDE.
- 4 THE RETENTION LEG IS A TEMPORARY FIX BEFORE SOLDERING
- 5 HOUSING MATERIAL : P.B.T(UL94V-0) / BLACK
- 6 CONTACT MATERIAL : PHO-BRONZE
- 7 CONTACT FINISH : NICKEL 0.00127 MIN THK. OVERALL SELECTIVE GOLD 0.00076 MIN OR 0.0002 MIN. THK ON CONTACT AREA AND TIN 0.001 MIN THK. ON TINE AREA.
- 8 RETENTION LEG FINISH:0.002 MIN TIN PL. OVER 0.001 MIN NICKEL PL.
- 9 RETENTION LEG MATERIAL:BRASS
- 10 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

6-	-4	60	29	36.83	41.00	44.23	48.14	Au PL. 0.00076 MIN.
6-	-3	50	24	30.48	34.65	37.88	41.72	
6-	-2	40	19	24.13	28.30	31.53	35.44	Au PL. 0.0002 MIN.
6-	-1	30	14	17.78	21.95	25.18	29.09	
	-4	60	29	36.83	41.00	44.23	48.14	Au PL. 0.0002 MIN.
	-3	50	24	30.48	34.65	37.88	41.72	
	-2	40	19	24.13	28.30	31.53	35.44	
5174217-1		30	14	17.78	21.95	25.18	29.09	
PART NUMBER	POS	n	A	B	C	D	REMARK	

GENERAL TOLERANCE
一般公差

10 ≥ : ±0.2
30 ≥ > 10: ±0.25
100 ≥ > 30: ±0.3
ANGLES: ±3°

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: 単位: 耗 mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差
	0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -
MATERIAL 材料	FINISH 仕上
SEE NOTE 5, 6, 9	SEE NOTE 7, 8

DWN GAVIN ZHANG 06JUL04	TE Connectivity	
CHK T. KAWAMAE 06JUL04		
APVD I. ENOMOTO 06JUL04	NAME 名称	
PRODUCT SPEC 製品規格 108-60036	PLUG ASSY (HORIZONTAL / W/LEG) AMPLIMITE .050 SERIES I B-TO-B CONN.	
APPLICATION SPEC 取付適用規格	SIZE A3	CAGE CODE 00779
WEIGHT	DRAWING NO 番号 C-5174217	RESTRICTED TO
CUSTOMER DRAWING	SCALE 尺度 2:1	SHEET 1 OF 1
	REV B	